

TECHNICAL DATA

Eldorado PR-5044T Neutral Peroxide Paint Remover

Description

Eldorado PR-5044T is an approved higher viscosity version of PR-5044, peroxide-activated paint and primer remover, for removal of durable polyurethane and epoxy paint systems. The higher viscosity prolongs contact time for spot stripping and for retention on vertical surfaces.

Material Properties

- Yellow, thick liquid
- Excellent cling to vertical and underside surfaces.
- Contains no chlorinated solvents.
- Approved by or conforms to: BAC5725, DPM 5549, D6-17487, Douglas CSD #1

Application Techniques

The preferred surface temperature for use of PR-5044T is 50° to 95°F. Apply a thick even layer of remover (about 1/32 to 1/16 inch) onto the coating to be removed. An air powered sprayer, brush, or paint roller maybe used to apply PR-5044T. Dwell time is dependent upon temperature and airflow, but expect from 1 to 16 hours. Once the stripper has loosened paint; scrub, and squeegee off loosened paint and stripper residues. If a second application of PR-5044T is required, apply after removing loosened paint.

Once operation is complete, surfaces must be cleaned. Wash the stripped surfaces with an alkaline aircraft cleaner. When washing with alkaline soap, pay close attention to remove all remover residues by directing the spray into or scrubbing skin laps and seams. Rinse all surfaces thoroughly.

Important: All parts of application equipment that come in contact with PR-5044T must be made of stainless steel or plastic, such as PVC, polyethylene, or polyester. Use plastic buckets and synthetic bristle brushes. Do not contaminate PR-5044T with other paint removers.

Caution: Produces Burns - bleaches skin upon exposure. Use with adequate ventilation and proper safety equipment. See MSDS for more details.

Caution: Used material contaminated with paint flakes and organic materials may undergo spontaneous pressure. Paint flakes must be rinsed with water to remove paint stripper prior to packaging in vented containers before disposal. See MSDS for more details..

Health Precautions

This product is safe to use and apply when recommended precautions are followed. Before using this product, read and understand the Material Safety Data Sheet (MSDS), which provides information on health, physical and environmental hazards, handling precautions and first aid recommendations. An MSDS is available on request. Avoid overexposure. Obtain medical care in case of extreme overexposure.

For industrial use only. Keep away from children.

Additional information can be found at:
www.ppgaerospace.com

For sales and ordering information call
1-800-AEROMIX (237-6649).

Eldorado PR-5044T Neutral Peroxide Paint Remover

All recommendations, statements, and technical data contained herein are based on tests we believe to be reliable and correct, but accuracy and completeness of said tests are not guaranteed and are not to be construed as a warranty, either expressed or implied. User shall rely on his own information and tests to determine suitability of the product for the intended use and assumes all risks and liability resulting from his use of the product. Seller's and manufacturer's sole responsibility shall be to replace that portion of the product of this manufacturer which proves to be defective. Neither seller nor manufacturer shall be liable to the buyer or any third person for any injury, loss, or damage directly or indirectly resulting from use of, or inability to use, the product. Recommendations or statements other than those contained in a written agreement signed by an officer of the manufacturer shall not be binding upon the manufacturer or seller.

Printed in U.S.A.

PRC-DeSoto International, Inc.
12780 San Fernando Road
Sylmar, CA 91342
Telephone (818) 362-6711
Toll Free (800) AEROMIX
www.ppgaerospace.com

Issue Date: 08/10
Supersedes: New
Lit: 4074