

TECHNICAL DATA

Eldorado PR-3451 Paint Remover

Description

Eldorado PR-3451 is a nonphenolic, ammonia-activated, viscous paint remover, particularly effective for removal of polyurethane and alkyd paints from aircraft surfaces.

Material Properties

- Nonflammable
- Safe on aluminum, cadmium, magnesium, ferrous alloys, and high-strength steel
- Effective for removal of acrylic, alkyd, polyurethane, and most epoxy paints
- Low chromate content
- Contains no phenols
- Approved by or conforms to: MIL-R-81294, Type II, Class 2

Application Techniques

Spray or brush PR-3451 onto surface to be stripped. Allow 20 minutes to 1 hour for paint to be loosened. Agitate to break remaining bond, then rinse with stream of water. Conditions of humidity and temperature will dictate dwell time. PR-3451 should remain in contact with the paint for as long as possible without drying. Clean stripped surface with ED-500 to remove all stripper residues.

PR-3451 contains dichloromethane, it must be used with adequate ventilation.

When application is made on a large-scale, full wash rack gear, consisting of rubber boots, gloves, face mask, and rubber clothing should be worn to avoid contact of material with skin. If skin contact occurs, wash immediately with soap and water.

Health Precautions

This product is safe to use and apply when recommended precautions are followed. Before using this product, read and understand the Material Safety Data Sheet (MSDS), which provides information on health, physical and environmental hazards, handling precautions and first aid recommendations. An MSDS is available on request. Avoid overexposure. Obtain medical care in case of extreme overexposure.

For industrial use only. Keep away from children.

**Additional information can be found at:
www.ppgaerospace.com**

**For sales and ordering information call
1-800-AEROMIX (237-6649).**

Eldorado PR-3451 Paint Remover

All recommendations, statements, and technical data contained herein are based on tests we believe to be reliable and correct, but accuracy and completeness of said tests are not guaranteed and are not to be construed as a warranty, either expressed or implied. User shall rely on his own information and tests to determine suitability of the product for the intended use and assumes all risks and liability resulting from his use of the product. Seller's and manufacturer's sole responsibility shall be to replace that portion of the product of this manufacturer which proves to be defective. Neither seller nor manufacturer shall be liable to the buyer or any third person for any injury, loss, or damage directly or indirectly resulting from use of, or inability to use, the product. Recommendations or statements other than those contained in a written agreement signed by an officer of the manufacturer shall not be binding upon the manufacturer or seller.

Printed in U.S.A.

PRC-DeSoto International, Inc.
12780 San Fernando Road
Sylmar, CA 91342
Telephone (818) 362-6711
Toll Free (800) AEROMIX
www.ppgaerospace.com

Issue Date: 10/11
Supersedes: 08/10
Lit: 4049