

TECHNICAL DATA

Eldorado PR-3500 Paint Remover, Epoxy Systems

Description

Eldorado PR-3500 is a high-performance, solvent-based, viscous stripper, used to strip aircraft primers, epoxy, polyurethane, and other organic coatings from metal surfaces.

Material Properties

- Nonflammable
- Low-vapor toxicity
- Contains phenol and sodium chromate
- Neutral pH
- Safe on aluminum, cadmium, magnesium, ferrous alloys, titanium and high strength steel
- Approved by or conforms to: MIL-R-81294, Type I, Class 1 and Type V, Class 1; AMS 1375, T.O. 1-1-8, Boeing D6, Douglas CSD #1, ARP 1755, China Aviation, Rolls-Royce, Embraer

Application Techniques

Works well at temperatures ranging from 45° to 95°F. Spray or brush undiluted PR-3500 paint stripper onto surface. Allow at least 15 minutes for the paint to be loosened. Agitate to dislodge loosened paint, then squeegee stripper residues and paint from the surface. Plastics sheeting placed under the aircraft have been found to be useful to facilitate the collection of paint stripper residue.

Conditions of humidity and temperature will dictate dwell time. Clean stripped surface with ED-500 to remove all stripper residues.

If PR-3500 accidentally contacts the skin, flood the affected area with water. If further treatment is required apply some ointment or salve to replace oils and soothe the skin. In case of contact with eyes, flush thoroughly with water and seek medical attention.

PR-3500 must be used with adequate ventilation, due to the high-chlorinated solvent content. When application is made on a large scale, full wash rack gear consisting of rubber boots, gloves, foul-weather gear, and facemask should be worn to minimize contact of the material with the skin.

Health Precautions

This product is safe to use and apply when recommended precautions are followed. Before using this product, read and understand the Material Safety Data Sheet (MSDS), which provides information on health, physical and environmental hazards, handling precautions and first aid recommendations. An MSDS is available on request. Avoid overexposure. Obtain medical care in case of extreme overexposure.

For industrial use only. Keep away from children.

**Additional information can be found at:
www.ppgaerospace.com**

**For sales and ordering information call
1-800-AEROMIX (237-6649).**

Eldorado PR-3500 Paint Remover, Epoxy Systems

All recommendations, statements, and technical data contained herein are based on tests we believe to be reliable and correct, but accuracy and completeness of said tests are not guaranteed and are not to be construed as a warranty, either expressed or implied. User shall rely on his own information and tests to determine suitability of the product for the intended use and assumes all risks and liability resulting from his use of the product. Seller's and manufacturer's sole responsibility shall be to replace that portion of the product of this manufacturer which proves to be defective. Neither seller nor manufacturer shall be liable to the buyer or any third person for any injury, loss, or damage directly or indirectly resulting from use of, or inability to use, the product. Recommendations or statements other than those contained in a written agreement signed by an officer of the manufacturer shall not be binding upon the manufacturer or seller.

Printed in U.S.A.

PRC-DeSoto International, Inc.
12780 San Fernando Road
Sylmar, CA 91342
Telephone (818) 362-6711
Toll Free (800) AEROMIX
www.ppgaerospace.com

Issue Date: 10/11
Supersedes: 08/10
Lit: 4050