

TECHNICAL DATA

Eldorado PR-4008 Paint Remover

Description

Eldorado PR-4008 is a viscous, acid-activated, phenolic paint remover, particularly effective for removal of polyurethane and epoxy paints from aircraft surfaces.

Material Properties

- Effective for removal of acrylic, alkyd, polyurethane, and epoxy paints
- Nonflammable
- Contains phenol
- Safe for use on aluminum, mild steel, titanium, and cad plate
- Approved by or conforms to: MIL-R-81903, Type II, Class 1, Boeing D6-17487, Douglas CSD #1

Application Techniques

Spray or brush PR-4008 onto surface to be stripped. Allow 20 minutes to 1 hour for paint to be loosened. Agitate to break remaining bond, then rinse with stream of water.

Conditions of humidity and temperature will dictate dwell time. Clean stripped surface with ED-500 to remove all stripper residues.

Avoid contamination with water. PR-4008 may cause pitting of aluminum or magnesium when contaminated with water. Do not use on magnesium or high-strength steel. Adequate ventilation is required, due to presence of chlorinated solvents. Protective clothing, such as face shields, rubber gloves, and rubber aprons, should be provided. In case of accidental contact with skin, wash thoroughly with soap and water, and rinse with alcohol containing 2% camphor. For eyes, flush with copious amounts of water, then seek medical attention.

Health Precautions

This product is safe to use and apply when recommended precautions are followed. Before using this product, read and understand the Material Safety Data Sheet (MSDS), which provides information on health, physical and environmental hazards, handling precautions and first aid recommendations. An MSDS is available on request. Avoid overexposure. Obtain medical care in case of extreme overexposure.

For industrial use only. Keep away from children.

**Additional information can be found at:
www.ppgaerospace.com**

**For sales and ordering information call
1-800-AEROMIX (237-6649).**

Eldorado PR-4008 Paint Remover

All recommendations, statements, and technical data contained herein are based on tests we believe to be reliable and correct, but accuracy and completeness of said tests are not guaranteed and are not to be construed as a warranty, either expressed or implied. User shall rely on his own information and tests to determine suitability of the product for the intended use and assumes all risks and liability resulting from his use of the product. Seller's and manufacturer's sole responsibility shall be to replace that portion of the product of this manufacturer which proves to be defective. Neither seller nor manufacturer shall be liable to the buyer or any third person for any injury, loss, or damage directly or indirectly resulting from use of, or inability to use, the product. Recommendations or statements other than those contained in a written agreement signed by an officer of the manufacturer shall not be binding upon the manufacturer or seller.

Printed in U.S.A.

PRC-DeSoto International, Inc.
12780 San Fernando Road
Sylmar, CA 91342
Telephone (818) 362-6711
Toll Free (800) AEROMIX
www.ppgaerospace.com

Issue Date: 10/11
Supersedes: 08/10
Lit: 4051