

TECHNICAL DATA

Eldorado Polish XM Aluminum Metal Polish

Description

Eldorado Polish XM is a viscous polish for aluminum surfaces. The abrasive nature of Polish XM enables it to remove tarnish and to produce a high-lasting polish on unpainted clad, aluminum surfaces. Polish XM is designed to be used for spot polishing or with power buffing equipment.

Material Properties

- Opaque, viscous liquid
- Flash Point: Above 190°F (87.7°C)
- Safe on aluminum alloys
- Mild odor; reduces worker fatigue
- Approved by or conforms to: AMS 1650; MIL-P-6888

Application Techniques

Apply Polish XM to the surface to be polished, or apply on the polish buffer pad. Buff the surface approximately 1 minute. Allow residues to dry. Buff with clean pads to remove residues and to achieve the desired finish. After polishing, apply a suitable solvent-type aircraft wax to protect the surface. Removal of oxides, prior to buffing, with Eldorado AC-12 will reduce buffing time.

Contains petroleum solvent and abrasive. A dust mask is required to avoid breathing abrasive particles. Avoid contact with skin and eyes through the use of rubber gloves and goggles. Do not use in confined spaces. In case of accidental contact with eyes, flush with plenty of water and contact physician. If accidentally ingested, seek medical attention.

Health Precautions

This product is safe to use and apply when recommended precautions are followed. Before using this product, read and understand the Material Safety Data Sheet (MSDS), which provides information on health, physical and environmental hazards, handling precautions and first aid recommendations. An MSDS is available on request. Avoid overexposure. Obtain medical care in case of extreme overexposure.

For industrial use only. Keep away from children.

**Additional information can be found at:
www.ppgaerospace.com**

**For sales and ordering information call
1-800-AEROMIX (237-6649).**

Eldorado Polish XM Aluminum Metal Polish

All recommendations, statements, and technical data contained herein are based on tests we believe to be reliable and correct, but accuracy and completeness of said tests are not guaranteed and are not to be construed as a warranty, either expressed or implied. User shall rely on his own information and tests to determine suitability of the product for the intended use and assumes all risks and liability resulting from his use of the product. Seller's and manufacturer's sole responsibility shall be to replace that portion of the product of this manufacturer which proves to be defective. Neither seller nor manufacturer shall be liable to the buyer or any third person for any injury, loss, or damage directly or indirectly resulting from use of, or inability to use, the product. Recommendations or statements other than those contained in a written agreement signed by an officer of the manufacturer shall not be binding upon the manufacturer or seller.

Printed in U.S.A.

PRC-DeSoto International, Inc.
12780 San Fernando Road
Sylmar, CA 91342
Telephone (818) 362-6711
Toll Free (800) AEROMIX
www.ppgaerospace.com

Issue Date: 09/11
Supersedes: 08/10
Lit: 4045