

# Matthews Clears

## Clear Characteristics

CONVENTIONAL CLEARS	Gloss Range 60° Meter					Specialty Characteristic
	Matte 0 - 4	Flat 5 - 9	Satin 10 - 29	Semi 30 - 79	Full 80+	
42 900SP	2 - 4					
6125SP	2 - 8					Tactile Feel
SOA 1643SP		5 - 10				
42 228SP		8 - 12				ADA Compliant
SOA 4158SP			12 - 18			ADA Compliant
SOA 365SP			25 - 35			
SOA 549SP				40 - 50		
SOA 570SP				50 - 60		
42 208SP					90 - 95	
SOA 6062SP			15 - 20			Anti-tarnish
42 260SP					90 - 95	Braco Anti-tarnish
SOA 4436SP		8 - 12				No UV Screen
SOA 5939SP				40 - 50		No UV Screen
<b>VOC COMPLIANT CLEARS</b>						
VOC 1471SP		7 - 10				
281 228SP			15 - 20			2.8 or 3.5 VOC
VOC 1427SP				50 - 60		
282 208SP					90 - 95	2.8 or 3.5 VOC
VOC 1454SP			15 - 20			Braco Anti-tarnish
282 260SP					90 - 95	Braco Anti-tarnish
VOC 1455SP					85 +	No UV Screen
*6178SP					90 +	Scratch & Chemical Resistant/Submersibility

\*Not intended for use as a coating for anti-fouling or use in marine applications.

Consult the corresponding Matthews Product Bulletin for the systems' application recommendations and performance characteristics.

**Important:**

The contents of this package may have to be blended with other components before the product can be used. Before opening the packages, be sure you understand the warning messages on the labels of all components, since the mixture will have the hazards of all its parts. Improper spray technique may result in a hazardous condition. Follow spray equipment manufacturer's instructions to prevent personal injury or fire. Follow directions for respirator use. Wear eye and skin protection. Observe all applicable precautions.

---

**See Material Safety Data Sheet and Labels for additional safety information and handling instructions.**

---

EMERGENCY MEDICAL OR SPILL CONTROL INFORMATION - US (412) 434-4515; CANADA (514) 645-1320; MEXICO 01-800-00-21-400

Materials described are designed for application by professional, trained personnel using proper equipment and are not intended for sale to the general public. Products mentioned may be hazardous and should only be used according to directions, while observing precautions and warning statements listed on label. Statements and methods described are based upon the best information and practices known to Matthews Paint. Procedures for applications mentioned are suggestions only and are not to be construed as representations or warranties as to performance, results, or fitness for any intended use, nor does Matthews Paint warrant freedom from patent infringement in the use of any formula or process set forth herein.

If you require technical assistance, please call us toll-free 800/323-6593.



**MATTHEWS PAINT**

*The World's Finest Coating For Architectural Signage*

760 Pittsburgh Drive  
Delaware, OH 43015  
Toll Free: 800/323-6593  
Toll Free FAX: 800/947-0377