

Type: Uncoated Tinted Insulating Glass
“Solexia™” + Clear by PPG Industries, Inc.

Outdoor Lite: “Solexia” (transparent) Float Glass by PPG Industries, Inc.

Indoor Lite: Clear (transparent) Float Glass

Tint Color: “Solexia” by PPG Industries, Inc.

Performance Values

Visible Light Transmission	U-Value Winter	U-Value Summer	SHGC	Shading Coefficient	Outdoor Visible Light Reflectance
69%	0.47	0.50	0.49	0.57	13%

Approved Manufacturers: PPG Certified Fabricator

Certification: Both lites to be Cradle to Cradle certified, minimum Silver Level, by McDonough Braungart Design Chemistry, LLC (MBDC www.mbdc.com).

Outdoor Appearance: Light Green color, low-reflective glass product

Insulating Unit Construction: 1/4” (6mm) glass + 1/2” (13mm) air space + 1/4” (6mm) glass

Type: Solar Control Low-E Clear Insulating Glass
“Solarban®” 70XL (2) “Solexia™” + Clear by PPG Industries, Inc.

Outdoor Lite: “Solexia” Glass by PPG Industries, Inc., Sputter Coated on second surface (2)

Indoor Lite: Clear Float Glass

Low-E Coating: “Solarban” 70XL Solar Control (Sputtered) by PPG Industries, Inc.

Location: Second Surface (2)

Performance Values

Visible Light Transmission	U-Value Winter	U-Value Summer	SHGC	Shading Coefficient	Outdoor Visible Light Reflectance
54%	0.28	0.26	0.25	0.29	10%

Approved Manufacturers: PPG Certified Fabricator

Certification: Both lites to be Cradle to Cradle certified, minimum Silver Level, by McDonough Braungart Design Chemistry, LLC (MBDC www.mbdc.com).

Outdoor Appearance: Light Green

Insulating Unit Construction: 1/4” (6mm) glass + 1/2” (13mm) air space + 1/4” (6mm) glass

Type: Solar Control Low-E Tinted Insulating Glass
"Solexia™" + "Solarban®" 70XL (3) by PPG Industries, Inc.

Outdoor Lite: "Solexia" Glass by PPG Industries, Inc.

Indoor Lite: "Starphire" Glass by PPG Industries, Inc., Sputter Coated on third surface (3) for annealed and some heat treated applications, depending on manufacturing process

Clear Glass by PPG Industries, Inc., Sputter Coated on third surface (3) for heat treated applications, depending on manufacturing process

Low-E Coating: "Solarban" 70XL Solar Control (Sputtered) by PPG Industries, Inc.

Location: Third Surface (3)

Performance Values

Visible Light Transmission	U-Value Winter	U-Value Summer	SHGC	Shading Coefficient	Outdoor Visible Light Reflectance
56%	0.28	0.26	0.32	0.37	11%

Approved Manufacturers: PPG Certified Fabricator

Certification: Both lites to be Cradle to Cradle certified, minimum Silver Level, by McDonough Braungart Design Chemistry, LLC (MBDC www.mbdc.com).

Outdoor Appearance: Emerald Green

Insulating Unit Construction: 1/4" (6mm) glass + 1/2" (13mm) air space + 1/4" (6mm) glass

Type: Solar Control Low-E Tinted Insulating Glass
"Solarban®" 60 (2) "Solexia™" + Clear by PPG Industries, Inc.

Outdoor Lite: "Solexia" Glass by PPG Industries, Inc., Sputter Coated on second surface (2)

Indoor Lite: Clear Float Glass

Low-E Coating: "Solarban" 60 Solar Control (Sputtered) by PPG Industries, Inc.

Location: Second Surface (2)

Performance Values

Visible Light Transmission	U-Value Winter	U-Value Summer	SHGC	Shading Coefficient	Outdoor Visible Light Reflectance
61%	0.29	0.27	0.32	0.36	10%

Approved Manufacturers: PPG Certified Fabricator

Certification: Both lites to be Cradle to Cradle certified, minimum Silver Level, by McDonough Braungart Design Chemistry, LLC (MBDC www.mbdc.com).

Outdoor Appearance: Light-green color, low-reflective glass product

Insulating Unit Construction: 1/4" (6mm) glass + 1/2" (13mm) air space + 1/4" (6mm) glass

Type: Solar Control Low-E Tinted Insulating Glass
“Solexia™” + “Solarban®” 60 (3) Clear by PPG Industries, Inc.

Outdoor Lite: “Solexia” Glass by PPG Industries, Inc.

Indoor Lite: Clear Float Glass, Sputter Coated on third surface (3)

Low-E Coating: “Solarban” 60 Solar Control (Sputtered) by PPG Industries, Inc.

Location: Third Surface (3)

Performance Values

Visible Light Transmission	U-Value Winter	U-Value Summer	SHGC	Shading Coefficient	Outdoor Visible Light Reflectance
61%	0.29	0.27	0.36	0.42	11%

Approved Manufacturers: PPG Certified Fabricator

Certification: Both lites to be Cradle to Cradle certified, minimum Silver Level, by McDonough Braungart Design Chemistry, LLC (MBDC www.mbdc.com).

Outdoor Appearance: Light Green color, low-reflective glass product

Insulating Unit Construction: 1/4” (6mm) glass + 1/2” (13mm) air space + 1/4” (6mm) glass

Type: Solar Control Low-E Tinted Insulating Glass
“Solarban®” z50 (2) “Optiblu®” + “Solexia™” by PPG Industries, Inc.

Outdoor Lite: “Solarban z50 (2) Optiblu” Glass by PPG Industries, Inc., Sputter Coated on second surface (2)

Indoor Lite: “Solexia” Glass by PPG Industries, Inc.

Low-E Coating: “Solarban” z50 Solar Control (Sputtered) by PPG Industries, Inc.

Location: Second Surface (2)

Performance Values

Visible Light Transmission	U-Value Winter	U-Value Summer	SHGC	Shading Coefficient	Outdoor Visible Light Reflectance
44%	0.29	0.27	0.30	0.35	8%

Approved Manufacturers: PPG Certified Fabricator

Certification: Both lites to be Cradle to Cradle certified, minimum Silver Level, by McDonough Braungart Design Chemistry, LLC (MBDC www.mbdc.com).

Outdoor Appearance: Blue Grass Gray

Insulating Unit Construction: 1/4” (6mm) glass + 1/2” (13mm) air space + 1/4” (6mm) glass

Type: Solar Control Low-E Tinted Insulating Glass
“Solexia™” + “Solarban®” z50 (3) “Optiblue®” by PPG Industries, Inc.

Outdoor Lite: “Solexia” Glass by PPG Industries, Inc.

Indoor Lite: “Solarban z50 (3) Optiblue” Glass by PPG Industries, Inc., Sputter Coated on third surface (3)

Low-E Coating: “Solarban” z50 Solar Control (Sputtered) by PPG Industries, Inc.

Location: Third Surface (3)

Performance Values

Visible Light Transmission	U-Value Winter	U-Value Summer	SHGC	Shading Coefficient	Outdoor Visible Light Reflectance
44%	0.29	0.27	0.35	0.41	10%

Approved Manufacturers: PPG Certified Fabricator

Certification: Both lites to be Cradle to Cradle certified, minimum Silver Level, by McDonough Braungart Design Chemistry, LLC (MBDC www.mbdc.com).

Outdoor Appearance: Blue Grass Gray

Insulating Unit Construction: 1/4” (6mm) glass + 1/2” (13mm) air space + 1/4” (6mm) glass

Type: Pyrolytic Low-E Tinted Insulating Glass
“Solexia™” + “Sungate®” 500 (3) Clear by PPG Industries, Inc.

Outdoor Lite: “Solexia” Glass by PPG Industries, Inc.

Indoor Lite: Clear Float Glass, Pyrolytic Coated on third surface (3)

Low-E Coating: “Sungate” 500 (Pyrolytic) by PPG Industries, Inc.

Location: Third Surface (3)

Performance Values

Visible Light Transmission	U-Value Winter	U-Value Summer	SHGC	Shading Coefficient	Outdoor Visible Light Reflectance
64%	0.35	0.35	0.44	0.51	14%

Approved Manufacturers: PPG Certified Fabricator

Certification: Both lites to be Cradle to Cradle certified, minimum Silver Level, by McDonough Braungart Design Chemistry, LLC (MBDC www.mbdc.com).

Outdoor Appearance: Light Green color, low-reflective glass product

Insulating Unit Construction: 1/4” (6mm) glass + 1/2” (13mm) air space + 1/4” (6mm) glass

Type: Reflective Tinted Insulating Glass
“Solarcool®” (2) “Solexia™” + Clear

Outdoor Lite: “Solarcool (2) Solexia” Glass by PPG Industries, Inc., Pyrolytic Coated on second surface (2)

Tint Color: “Solexia” by PPG Industries, Inc.

Indoor Lite: Clear Float Glass

Reflective Coating: “Solarcool” (Pyrolytic) by PPG Industries, Inc.

Location: Second Surface (2)

Performance Values

Visible Light Transmission	U-Value Winter	U-Value Summer	SHGC	Shading Coefficient	Outdoor Visible Light Reflectance
27%	0.48	0.50	0.31	0.36	24%

Approved Manufacturers: PPG Certified Fabricator

Certification: Both lites to be Cradle to Cradle certified, minimum Silver Level, by McDonough Braungart Design Chemistry, LLC (MBDC www.mbdc.com).

Outdoor Appearance: Light Green Metallic

Insulating Unit Construction: 1/4” (6mm) glass + 1/2” (13mm) air space + 1/4” (6mm) glass

Type: Reflective Solar Control Low-E Insulating Glass

“Solarcool®” (2) “Solexia™” + “Solarban®” 70XL (3) by PPG Industries, Inc.

Outdoor Lite: “Solarcool (2) Solexia” Glass by PPG Industries, Inc., Pyrolytic Coated on second surface (2)

Tint Color: “Solexia” by PPG Industries, Inc.

Indoor Lite: “Starphire” Glass by PPG Industries, Inc., Sputter Coated on third surface (3) for annealed and some heat treated applications, depending on manufacturing process

Clear Glass by PPG Industries, Inc., Sputter Coated on third surface (3) for heat treated applications, depending on manufacturing process

Low-E Coating: “Solarban” 70XL Solar Control (Sputtered) by PPG Industries, Inc.

Location: Third Surface (3)

Reflective Coating: “Solarcool” (Pyrolytic) by PPG Industries, Inc.

Location: Second Surface (2)

Performance Values

Visible Light Transmission	U-Value Winter	U-Value Summer	SHGC	Shading Coefficient	Outdoor Visible Light Reflectance
22%	0.28	0.26	0.17	0.20	24%

Approved Manufacturers: PPG Certified Fabricator

Certification: Both lites to be Cradle to Cradle certified, minimum Silver Level, by McDonough Braungart Design Chemistry, LLC (MBDC www.mbdc.com).

Outdoor Appearance: Natural Green Metallic

Insulating Unit Construction: 1/4” (6mm) glass + 1/2” (13mm) air space + 1/4” (6mm) glass

Type: Reflective Tinted Solar Control Low-E Insulating Glass
“Solarcool®” (2) “Solexia™” + “Solarban®” 60 (3) Clear by PPG Industries, Inc.

Outdoor Lite: “Solarcool (2) Solexia” Glass by PPG Industries, Inc., Pyrolytic Coated on second surface (2)

Tint Color: “Solexia” by PPG Industries, Inc.

Indoor Lite: Clear Float Glass, Sputter Coated on third surface (3)

Low-E Coating: “Solarban” 60 Solar Control (Sputtered) by PPG Industries, Inc.

Location: Third Surface (3)

Reflective Coating: “Solarcool” (Pyrolytic) by PPG Industries, Inc.

Location: Second Surface (2)

Performance Values

Visible Light Transmission	U-Value Winter	U-Value Summer	SHGC	Shading Coefficient	Outdoor Visible Light Reflectance
24%	0.29	0.27	0.19	0.22	24%

Approved Manufacturers: PPG Certified Fabricator

Certification: Both lites to be Cradle to Cradle certified, minimum Silver Level, by McDonough Braungart Design Chemistry, LLC (MBDC www.mbdc.com).

Outdoor Appearance: Natural Green Metallic

Insulating Unit Construction: 1/4” (6mm) glass + 1/2” (13mm) air space + 1/4” (6mm) glass

Type: Solar Control Low-E Insulating Glass

“Solarcool®” (2) “Solexia™” + “Solarban®” z50 (3) “Optiblue®” by PPG Industries, Inc.

Outdoor Lite: “Solarcool (2) Solexia” Glass by PPG Industries, Inc., Pyrolytic Coated on second surface (2)

Tint Color: “Solexia” by PPG Industries, Inc.

Indoor Lite: “Solarban z50 (3) Optiblue” Glass by PPG Industries, Inc., Sputter Coated on third surface (3)

Low-E Coating: “Solarban” z50 Solar Control (Sputtered) by PPG Industries, Inc.

Location: Third Surface (3)

Reflective Coating: “Solarcool” (Pyrolytic) by PPG Industries, Inc.

Location: Second Surface (2)

Performance Values

Visible Light Transmission	U-Value Winter	U-Value Summer	SHGC	Shading Coefficient	Outdoor Visible Light Reflectance
17.1	0.29	0.27	0.19	0.21	23%

Approved Manufacturers: PPG Certified Fabricator

Certification: Both lites to be Cradle to Cradle certified, minimum Silver Level, by McDonough Braungart Design Chemistry, LLC (MBDC www.mbdc.com).

Outdoor Appearance: Natural Green Metallic

Insulating Unit Construction: 1/4” (6mm) glass + 1/2” (13mm) air space + 1/4” (6mm) glass

Type: Reflective Tinted Low-E Insulating Glass

“Solarcool®” (2) “Solexia™” + “Sungate®” 500 (3) Clear by PPG Industries, Inc.

Outdoor Lite: “Solarcool (2) Solexia” Glass by PPG Industries, Inc., Pyrolytic Coated on second surface (2)

Tint Color: “Solexia” by PPG Industries, Inc.

Indoor Lite: Clear Float Glass, Pyrolytic Coated on third surface (3)

Low-E Coating: “Sungate” 500 (Pyrolytic) by PPG Industries, Inc.

Location: Third Surface (3)

Reflective Coating: “Solarcool” (Pyrolytic) by PPG Industries, Inc.

Location: Second Surface (2)

Performance Values

Visible Light Transmission	U-Value Winter	U-Value Summer	SHGC	Shading Coefficient	Outdoor Visible Light Reflectance
25%	0.35	0.35	0.26	0.31	24%

Approved Manufacturers: PPG Certified Fabricator

Certification: Both lites to be Cradle to Cradle certified, minimum Silver Level, by McDonough Braungart Design Chemistry, LLC (MBDC www.mbdc.com).

Outdoor Appearance: Light Green Metallic

Insulating Unit Construction: 1/4” (6mm) glass + 1/2” (13mm) air space + 1/4” (6mm) glass