

**Type: Solar Control Ultra-Clear Low-E Insulating Glass**  
**“Solarban” 60 (2) “Starphire” + “Starphire”** by PPG Industries, Inc.

**Outdoor Lite: “Starphire”** Glass by PPG Industries, Inc., Sputter Coated on second surface (2)

**Indoor Lite: “Starphire”** Float Glass

**Low-E Coating: “Solarban” 60** Solar Control (Sputtered) by PPG Industries, Inc.

**Location:** Second Surface (2)

**Performance Values**

Visible Light Transmission	U-Value Winter	U-Value Summer	SHGC	Shading Coefficient	Outdoor Visible Light Reflectance
74%	0.29	0.27	0.40	0.46	11%

**Approved Manufacturers:** PPG Certified Fabricator

**Certification:** Both lites to be Cradle to Cradle certified, minimum Silver Level, by McDonough Braungart Design Chemistry, LLC (MBDC [www.mbdc.com](http://www.mbdc.com)).

**Outdoor Appearance:** Ultra-Clear

**Insulating Unit Construction:** 1/4” (6mm) glass + 1/2” (13mm) air space + 1/4” (6mm) glass

**Type: Uncoated Ultra-Clear Float Glass**

**“Starphire” + “Starphire”** by PPG Industries, Inc.

**Outdoor Lite: “Starphire”** (ultra-clear) Float Glass by PPG Industries, Inc.

**Indoor Lite: “Starphire”** (ultra-clear) Float Glass by PPG Industries, Inc.

**Performance Values**

Visible Light Transmission	U-Value Winter	U-Value Summer	SHGC	Shading Coefficient	Outdoor Visible Light Reflectance
84%	0.47	0.50	0.82	0.94	15%

**Certification:** Both lites to be Cradle to Cradle certified, minimum Silver Level, by McDonough Braungart Design Chemistry, LLC (MBDC [www.mbdc.com](http://www.mbdc.com)).

**Outdoor Appearance:** Ultra-clear

**Insulating Unit Construction:** 1/4” (6mm) glass + 1/2” (13mm) air space + 1/4” (6mm) glass